



Low Temperature B.O.D. Incubator, SRI6P-2 (220V)

Product #:

ZAR Price: Ships within 3-5 weeks 2636202

Contact Hach

The Model SRI6P-2 B.O.D. incubator is thermoelectric cooled, eliminating the need for a refrigeration compressor. The incubators include a mechanical convection system to ensure even air distribution, digital temperature set controller, over temperature limit control, and a temperature display. Two 75 pound capacity shelves are included. A one amp interior outlet allows the use of shakers, stirrers, roller bottles or BODTrak apparatus.

Low Temperature Incubators are ideal for testing sewage and wastewater as well as other low room temperature applications. 220V

Exterior dimensions: 30 x 31.5 x 33.5 in (76.2 x 80.01 x 85.09 cm)

Innovative peltier cooling technology

Eliminates the need for a refrigeration compressor

Energy efficient

The SRI6P-2 uses 78% less power than alternative models and reduce rppm air conditioning loads by 75%

Ideal for Biochemical Oxygen Demand Meets APHA specifications for B.O.D, 120 bottle capacity

Temperature set controller Includes an over-temperature limit control

Mechanical convection system

Ensures even air distribution

Specifications

Accuracy:	\pm 0.5 °C at 20 °C Temperature Uniformity
Capacity:	120 BOD Bottles
Electrical Specifications:	Volts: 200-240V
Manual Languages:	English
Method:	8043
Temperature Range:	15 - 40 °C
Weight:	111.1 kg Shipping Weight
	56.7 kg Net Weight
	JU.7 Kg Ivel Weight
What's included?:	Two 75 pound capacity shelves

What's included?

Two 75 pound capacity shelvesAdjustable leveling feet