



## 8362sc High Purity Water pH Panel

**Product #:** 6178000  
**ZAR Price:** Contact Hach  
**Ships within 1 week**

### Simple to Integrate. Simple to Operate.

An integral part of a complete water analytics system designed for the Power industry. A broad range of product options made to work together as flexible solutions meets your unique needs. The comprehensive approach saves you time on design, installation, training, maintenance, and operation.

**Streamline sample panel design with this compact sensor that saves valuable space.**

**Accuracy ensured by self-pressurising electrodes and platinum RTD temperature sensor.**

**Self-pressurising electrodes are ready to operate and require virtually no maintenance.**

**Reduce drift common in less sophisticated probes.**

**Compact design reduces footprint in areas where space is extremely valuable.**

---

### Specifications

Cable Length:	7.7 m, supplied
Contents:	316 stainless steel back panel with pH or ORP sensor, flowmeter, and junction box Temperature probe: Pt100
Dimensions (H x W x D):	305 mm x 384 mm x 166 mm
Flow Rate:	100 to 300 mL/min
Measuring Range ORP:	at 0 - 50 °C
Measuring range pH:	2 - 12 pH at 0 - 80°C
Operating Humidity:	0 - 100 % (non-condensing)
Operating Pressure:	4 bar (58 psi) maximum at 25 °C
Operating temperature range:	0 - 60 °C
Parameter:	pH
pH Accuracy:	± 0.01 pH
Repeatability:	0.01 pH at 25 °C (constant flow)
Temperature Accuracy:	0.1 °C between 0 - 80 °C
Temperature Range:	0 - 80 °C
Temperature Sensor :	Pt100
Warranty:	12 months

Weight:

3.6 kg